

SG PLATINUM ADVANCE TILE ADHESIVE

High Polymer Modified Cementitious Tile Adhesive

SG Platinum Advance Tile Adhesive is a high polymer modified cementitious adhesive offering superior bond strength, slip resistance, and extended open time. Ideal for tile-on-tile applications and demanding interior as well as exterior installations.

Usage Details

Application Area	Usage Context	Substrates	Tile Types	Max. Tile Size	Max. Wall Height
Internal Floors & Walls	Residential & Commercial Applications	Cement Plaster, Gypsum Plaster, Screeds, Concrete, Existing Tiles, Drywalls	Ceramic, Vitrified, Glass Mosaic, Terracotta, Natural Stone, Large Format Tiles, Thin Tiles	Up to 90×90 cm (at 3mm thickness) 2X4, 5X2.5 FLOOR/WALL,	Suitable for High-Rise Applications

Technical Details

Conforms To	Physical Form	Open Time	Setting Time	Coverage***	Adjustment Time
Type 2, C2TF, S1T, ISO 13007 C2TF, EN 12004 C2TF	Grey / White Powder	20-25 Minutes	24 Hours	Approx. 90-100 Sq.Ft./40 Kg Bag at 3mm Thickness	25-30 Minutes



Sag Resistance



Water Resistance



High Polymer Modified



Easy To Mix And Apply



Features

- Low Voc
- Durability
- Large tiles
- For tile on tile
- Easy to apply
- Trowel application
- Low Consumption
- Polymer modified additives